



## SECTION 5

# SYPHILIS

## SECTION 5 | Syphilis

| Description      | Cat No.  | Methodology                                                                                    | Size                             | Storage  |
|------------------|----------|------------------------------------------------------------------------------------------------|----------------------------------|----------|
| RPR              | SYCA0002 | Reagent Only                                                                                   | 2ml (100T)                       | 2 - 8 °C |
|                  | SYCA0005 |                                                                                                | 5ml (250T)                       | 2 - 8 °C |
|                  | SYCA0010 |                                                                                                | 10ml (500T)                      | 2 - 8 °C |
|                  | SYCA0100 |                                                                                                | 100ml (5000T)                    | 2 - 8 °C |
|                  | SYCA1000 |                                                                                                | 1000ml (50,000T)                 | 2 - 8 °C |
| RPR              | SYRPR025 | Positive & Negative Control, Pipette/<br>Stirrers, Test Cards, Dispensing Bottle<br>and Needle | 25 Tests                         | 2 - 8 °C |
|                  | SYRPR050 |                                                                                                | 50 Tests                         | 2 - 8 °C |
|                  | SYRPR100 |                                                                                                | 100 Tests                        | 2 - 8 °C |
|                  | SYRPR500 |                                                                                                | 500 Tests                        | 2 - 8 °C |
| Syphilis Control | SYPN0010 | Positive & Negative Controls                                                                   | 2 x 5 x 1ml                      | 2 - 8 °C |
| TPHA             | SYTP0100 | TPHA with +ve and -ve Controls                                                                 | 100T                             | 2 - 8 °C |
|                  | SYTP0200 |                                                                                                | 200T                             | 2 - 8 °C |
| VDRL             | SYVD0005 | Positive & Negative Controls                                                                   | 1 x 5ml VDRL; 1 x<br>60ml Buffer | 2 - 8 °C |